

Standard Specification								
Model	Unit	BK350	BK450	BK530	BK680	BK750	BK850	BK1000
Suitable Excavator	ton	0.8-2.5	1.2-3.0	2.5-4.5	4-7	6-9	7-14	10-15
Operating Weight	Side type	kg	77	99	132	275	418	842
	Top type	kg	77	121	148	321	407	979
	Box type	kg	113	139	168	325	413	948
	Backhoe loader type	kg				305	388	
	Skid Steer Loader	kg			280	380	467	
Required Oil Flow	l/min	15-30	20-40	25-50	40-70	50-90	60-100	80-110
Setting Pressure	bar	150	150	150	170	180	190	200
Operating pressure	bar	90-120	90-120	90-120	110-140	120-150	130-160	150-170
Impact Energy	Joule	203	271	406	677	1017	1355	2033
Impact Rate	bpm	800-1400	700-1200	600-1100	500-900	400-800	400-800	350-700
Hose Diameter	inch	1/2	1/2	1/2	1/2	1/2	3/4	3/4
Noise level	dB	106	107	109	109	115	112	114
Tool Diameter	mm	35	45	53	68	75	85	100

Model	Unit	BK1250	BK1350	BK1400	BK1400A	BK1550	BK1650	BK1750
Suitable Excavator	ton	15-18	18-26	18-26	18-26	28-35	30-40	35-40
Operating Weight	Side type	kg	1381	1609	1950	1950	2655	4167
	Top type	kg	1463	1698	2050	2050	3059	4216
	Box type	kg	1427	1650	1978	1978	2896	4390
Required Oil Flow	l/min	90-120	100-150	120-180	120-180	180-240	200-260	210-290
Setting Pressure	bar	210	210-230	210-230	210-230	240-260	240-260	260-280
Operating pressure	bar	150-170	160-180	160-180	160-180	180-200	180-200	180-200
Impact Energy	Joule	2711	3423	4067	4067	6779	8812	12202
Impact Rate	bpm	350-650	350-600	350-500	350-500	300-450	250-400	250-350
Hose Diameter	inch	1	1	1	1	1-1/4	1-1/4	1-1/4
Noise level	dB	115	120	118	118	123	123	125
Tool Diameter	mm	125	135	140	140	155	165	175

Notice: Operating weight: hammer include chisel weight.